

Cold water meters for vertical pipes



The TOPAS PMKF / S series of velocity flowmeters is based on the well-established multi-jet measuring principle.

The measuring principle is insensitive to flow turbulences. SAPHIR bearings each side of the impeller wheel ensure the highest possible accuracy throughout the entire operating life of the meter. Versions for vertical mounting for both rising (R) and falling (F) pipes available.

Your benefits...

- The uniform flow of the impeller wheel ensures that even the smallest flowrates can be detected.
- Accurate flow measurement significantly increases the value of the system over its entire operating life.
- The roller counter can be rotated in any position required for reading off values easily.

Falling pipe version	PMKF**	PMKF**	PMKF	PMKF
DN mm	20	25	32	40
Qn m3/h	2.5	3.5	5	10
Standard	93043	93045	93047	93049
With reed pulser RH1	89130	89131	89132	89183
With reed pulser RH100	89171	89175	89179	89182

Rising pipe version	PMKS**	PMKS**	PMKS	PMKS
DN mm	20	25	32	40
Qn m3/h	2.5	3.5	5	10
Standard	93050	93052	93054	93056
With reed pulser RH1	89127	89131	89129	89153
With reed pulser RH100	89141	89145	89149	89152

Accessories

Threaded connections with lip		
Designation	Version	Art. No.
VSR 3/4"	DN 20	81164
VSR 1"	DN 25	81167
VSR 1 1/4"	DN 32	81170
VSR 1 1/2"	DN 40	81179

Ranger Instrument Co Ltd
Rutherford Road Basinstoke RG24 8PG
Tel 01256 464911 Fax 01256 464366 Email ranger@bayham.demon.co.uk